



Interactive Touch Screen Kiosk

Increase the satisfaction of your customers or visitors with a wayfinding kiosk in your business

Main features

- Free-standing design with option to bolt down base plate
- Power & data feed from rear panel or floor through the base plate
- Anti-Glare protection glass over the screen
- Key lockable access service door
- Ergonomic and compact structure
- User friendly, easy for maintenance



Technical Specifications

Screen

Screen Size	32" K32VR 43" K43VR
Resolution	1920x1080
Brightness	450 cd/m2
Aspect Ratio	16:9
Contrast Ratio	5000:1
Viewing Angle	178:178
Response Time	8ms

Touch

Touch Technology	PCAP - Projected Capacitive
Touch Points	Multi Touch
Response Time	8 ms
OS	Windows, Linux
Protection Glass	Tempered Anti Glare
Touch interface	USB
Touch method	finger

Other

Application	Indoor
Colour	RAL 7047 Grey (optional)
Installation	Floor bolting / Free Standing
Enclosure	Metal
Working temperature	0°C~50°C
Power supply	AC 100-240V 50/60HZ



Touch technology - Capacitive

The Projective Capacitive (PCAP) touch technology with 12 touch points ensures a seamless and accurate touch response. With its AMVA3 LED panel, it offers exceptional colour performance, high contrast and wide viewing angles.

This technology uses a sensor-grid of micro-fine wires integrated into the glass that covers the screen. Touch is detected because electrical characteristics of the sensor grid change when human finger is placed on the glass. Thanks to the glass overlay this technology is highly durable, and the touch function remains unaffected even if the glass is scratched.



Smart Design

The sleek look is achieved with a striking aluminium surround and edge-to-edge vandal proof tempered glass front panel




Plug and Play

If there is no internet access available the screen can still be updated thanks to their backup USB update option.



24/7 Commercial Use

A commercial grade panel, with a lifespan of 50,000 hours and high quality components ensure that this display can be in constant use 24/7.



Dimension (mm)

Size	Model Name	A	B	C
32"	K32VR	900	761	1181
43"	K43VR	1140	900	1200



Temas Technology Co., Ltd.
 Serifali Mahallesi, Kible Sokak, No: 29 34775
 Yukarı Dudullu / Umraniye / İstanbul / Türkiye
 Tel +90 216 314 54 54 - Fax +90 216 394 44 98
info@temasteknoloji.com.tr - www.temasteknoloji.com.tr